

ACOT


ACID PRODUCTS



HIGHLY CONCENTRATED BUFFERED ACID DETERGENT

FEATURES AND USE

ACOT grants a complete and safe removal of mineral salts from cotto tiles pores. Washing with ACOT is essential to remove the white efflorescence from new floors. ACOT can be used to remove encrustations from grés/porcelain stoneware tiles, clinker and smooth stone floors.



METHOD OF USE

Before being treated with a primer, a sealant or wax, cotto tiles floors must undergo a heavy wash treatment with an acid product. Perform this treatment only when floor is completely dry, this means about 20-40 days after the laying. Under favorable weather conditions floor's drying time shall be shorter.

- 1) Washing with ACOT: wash the floor with a 10-30% (1000-3000g in 10L water) solution. After this operation, rinse using a solution of MISTRAL at 1 to 3% of (100-300g in 10L of water) to neutralize any accidental acid residue left on the cotto tiles.
- 2) If the "acid wash" has been carried out properly, there must not be any mineral salts "flowering" on the floor's surface. If that happens, repeat the washing treatment.
- 3) After the "acid wash", dry the floor thoroughly. In dry climate or if the heating system is on, the floor will dry out completely in three days.

DILUTION

First treatment: from 10% to 30% (1000-3000g in 10L water)

To remove cement or mortar residues after masonry: 5% (500g in 10L water)

PACK SIZE



Art. code AC94 P10

10kg

TECHNICAL DATA

Physical state: liquid

Colour: red

Odour: technical

pH: 0,50

Density: 1,150 +/- 0,025 Kg/L

COMPOSITION

See safety data sheet. Ingredients compliant with CE Reg. 648/2004

CAUTIONS

See safety data sheet.

PROFESSIONAL USE



AR-CO CHIMICA SRL Via Canalazzo, 22/24 - 41036 Medolla - ITALY
Tel. +39 0535 58890 - info@arcochimica.it www.arcochimica.it