

COTTO FLOORS

FADO

WATER SILANIC EMULSION FOR PRETREATMENT OF COTTO TILES AND POROUS STONE FLOORS



FEATURES AND USE

FADO is used on all types of cotto tiles floors and other building surfaces with high/medium absorption. The pretreatment has the advantage to remove easier stuccowork residue from floors before cleaning with acid solution.

FADO pretreatment is suggested to avoid larger quantities consumption of acid product and longer operating time.

Without pretreatment the floor gets wet through to the depths and requires longer to dry, thus delaying successive treatment.

It is also possible that because of excessive imbibition, the cotto tiles floor may show ugly dark stains (oxidation).

METHOD OF USE & DILUTION:

Shake well before use. Apply FADO undiluted on the surface using a fleece or spray with a low pressure spray gun. The consumption of FADO is approximately 1 lt per 8-10 sq/mt of floor.

After at least 8-12 hours from of pre-treatment application, wash the surface with SUPRACID. Ready to use.

PACK SIZE:

Jerrycan 5Kg – 4 pcs/carton

TECHNICAL DATA:

Physical state: liquid

Colour: white

Odour: weak

pH: 6,50 ± 1,00

Specific weight: 989 g/L

COMPOSITION:

See safety data sheet. Ingredients compliant with CE 648/2004

CAUTIONS:



WARNING



AR-CO CHIMICA s.r.l. Via Canalazzo, 22/24 – 41036 MEDOLLA (MO)
Tel 0535.58890 – info@arcochimica.it – www.arcochimica.it

PROFESSIONAL USE