	HIMICA S.R.L.	Revision nr. 1
	Dated 30/12/2014	
		Printed on 02/03/2015
l l	GOTA	Page n. 1/10
	Cofety data about	
	Safety data sheet	
SECTION 1. Identification of the sub	stance/mixture and of the company/under	taking
1.1. Product identifier Product name	GOTA	
Flouderhame	GOTA	
1.2. Relevant identified uses of the substance or n		
	FOR INDUSTRIAL / PROFESSIONAL USING GREASER DETERGENT WITH CONTROLLED FOAMING A	CTION
1.3. Details of the supplier of the safety data sheet Name	AR-CO CHIMICA S.R.L.	
Full address	Via Canalazzo 22/24	
District and Country	41036 MEDOLLA (MO) ITALY	
	Tel. +39 053558890	
	Fax +39 053558898	
e-mail address of the competent person		
responsible for the Safety Data Sheet Product distribution by	reach@arcochimica.it AR-CO CHIMICA	
1.4. Emergency telephone number	Numeri telefeniai dai principali Contri Antivalani italiani	( attivi 24/24 are)
For urgent inquiries refer to	Numeri telefonici dei principali Centri Antiveleni italiani Centro Antiveleni di Milano 02 66101029 (CAV Ospedale	
	(H24) Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fond	taziono Maugori - Pavia)
	Centro Antiveleni di Bergamo 800 883300 (CAV Ospeda	li Riuniti - Bergamo)
	Centro Antiveleni di Firenze 055 7947819 (CAV Ospedal Centro Antiveleni di Roma 06 3054343 (CAV Policlinico	
	Centro Antiveleni di Roma 06 49978000 (CAV Policlinico	o Umberto I - Roma)
	Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale AR-CO CHIMICA	Cardarelli - Napoli)
	+39 0535558890 ( ORE UFFICIO / OFFICE HOURS 08:00-1	2:30 / 14:00-17:30 )

# **SECTION 2.** Hazards identification.

### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:	
Eye Dam. 1	H318
Skin Irrit. 2	H315

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

Xi

	AR-CO C	HIMICA S.R.	.L.	Revision nr. 1
		GOTA		Dated 30/12/2014 Printed on 02/03/2015
		GUIA		Page n. 2/10
R phrases: 36				
The full wording of the R	lisk (R) and hazard (H) phrase	s is given in section	16 of the sheet.	
2.2. Label elements.				
Hazard labelling pursual	nt to EC Regulation 1272/2008	(CLP) and subseq	uent amendments and suppleme	nts.
Hazard pictograms:				
Signal words:	Danger			
Hazard statements:				
H318 H315	Causes serious eye dama Causes skin irritation.	age.		
Precautionary statement	ts:			
P280 P302+P352 P310	Wear protective gloves / p IF ON SKIN: Wash with p Immediately call a POISC	lenty of soap and w		
Contains:	Benzenesulfonic acid,C10	0-13-alkyl derivates	sodium salt	
2.3. Other hazards.				
Information not available	3.			
SECTION 3. Co	mposition/informatio	on on ingredie	ents.	
3.1. Substances.				
Information not relevant.				
3.2. Mixtures.				
Contains:				
Identification. PENTABASIC SODIU	M TRIPHOSPHATE	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
CAS. 7758-29-4		1 - 5	Xi R36/37/38	Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335
EC. 231-838-7 INDEX				

Reg. no. 01-2119430450-54

Benzenesulfonic acid,C10-13-alkyl derivates sodium salt

	Revision nr. 1 Dated 30/12/2014		
	GOTA		Printed on 02/03/2015
			Page n. 3/10
CAS. 68411-30-3	3 - 5	Xn R22, Xi R38, Xi R41	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315
EC. 270-115-0			1010
INDEX			
Reg. no. 01-2119489428-22-XXXX			
COCOA FATTY ACIDS, POTASSIUM	SALTS		
CAS. 61789-30-8 EC. 263-049-9	1 - 5	Xi R36/38	Eye Irrit. 2 H319, Skin Irrit. 2 H315
INDEX			
DIPROPYLENE GLYCOL MONOMET	HYL ETHER		
CAS. 34590-94-8	0,5 - 1		Substance with a community workplace exposure limit.
EC. 252-104-2			
INDEX			
Reg. no. 01 2119450011-60			
AMMONIA			
CAS. 1336-21-6	0 - 0,5	C R34, N R50, Note B	Skin Corr. 1B H314, STOT SE 3 H335, Aquatic Acute 1 H400 M=1, Note B
EC. 215-647-6			
INDEX. 007-001-01-2			
Reg. no. 01-2119488876-14-0000			

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet. T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = ExtremelyFlammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

## **SECTION 4. First aid measures.**

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## **SECTION 5. Firefighting measures.**

### 5.1. Extinguishing media.

### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

Revision nr. 1 Dated 30/12/2014
Printed on 02/03/2015 Page n. 4/10
-

### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6.** Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

### **SECTION 7. Handling and storage.**

### 7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

AR-CO CHIMICA S.R.L.	Revision nr. 1 Dated 30/12/2014
GOTA	Printed on 02/03/2015 Page n. 5/10

Information not available.

## **SECTION 8. Exposure controls/personal protection.**

### 8.1. Control parameters.

Regulatory References:

United Kingdom	EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as
	amended).
Éire	Code of Practice Chemical Agent Regulations 2011.
OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive
	2000/39/EC.
TLV-ACGIH	ACGIH 2012

### DIPROPYLENE GLYCOL MONOMETHYL ETHER

Threshold Limit Value.						
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		606	100	909	150	SKIN
OEL	EU	308	50			SKIN
OEL	IRL	308	50			SKIN
WEL	UK	308	50			SKIN

Α	N	۱٨	٨C	)N	IA

Threshold Limit Value. Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		17	25	24	35	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

AR-CO CHIMICA S.R.L.	Revision nr. 1
	Dated 30/12/2014
GOTA	Printed on 02/03/2015 Page n. 6/10

#### EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### **SECTION 9.** Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance Colour Odour Odour threshold. pH. Melting point / freezing point. Initial boiling point. Boiling range. Flash point. Evaporation Rate Flammability of solids and gases Lower inflammability limit. Upper inflammability limit. Upper explosive limit. Upper explosive limit. Upper explosive limit. Vapour pressure. Vapour density Relative density. Solubility Partition coefficient: n-octanol/water Auto-ignition temperature.	viscous liquid green CITRUS / BALSAMIC Not available. 10,10 +/- 0,50 Not available. Not available.
Auto-ignition temperature.	Not available.
Viscosity	Not available. Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

### 9.2. Other information.

Information not available.

## **SECTION 10. Stability and reactivity.**

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

AMMONIA: corrodes aluminium, iron, zinc, copper and their alloys.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

# **AR-CO CHIMICA S.R.L.**

Revision nr. 1

Dated 30/12/2014 Printed on 02/03/2015

## GOTA

Page n. 7/10

No hazardous reactions are foreseeable in normal conditions of use and storage.

AMMONIA: risk of explosion on contact with strong acids and iodine. Can react dangerously with strong bases .

### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials.

AMMONIA: silver, lead, zinc and their salts; hydrochloric acid, nitric acid, oleum, halogens, acrolein, nitromethane and acrylic acid.

10.6. Hazardous decomposition products.

AMMONIA: nitric oxides.

## **SECTION 11. Toxicological information.**

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory trait. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

AMMONIA LD50 (Oral). 350 mg/kg Rat

## **SECTION 12. Ecological information.**

12.1. Toxicity.

AMMONIA LC50 - for Fish. 47 mg/l/96h Channa punctata EC50 - for Crustacea. 20 mg/l/48h Daphnia magna

### 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

AR-CO CHIMICA S.R.L.	Revision nr. 1
	Dated 30/12/2014
GOTA	Printed on 02/03/2015
	Page n. 8/10

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%. **12.6. Other adverse effects.** 

Information not available.

## **SECTION 13. Disposal considerations.**

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

CONTAMINĂTED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### **SECTION 14. Transport information.**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

## **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

None.

3

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product. Point.

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

# AR-CO CHIMICA S.R.L.

Revision nr. 1

Dated 30/12/2014 Printed on 02/03/2015

# GOTA

Page n. 9/10

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Ingredients according to Regulation (EC) No 648/2004

less than 5 % phosphates, anionic surfactants, non-ionic surfactants, soap

perfumes, Limonene, Linalool

preservation agents : 1,2-benzisotiazol-3(2H)-one / 2-metil-2H-isotiazol-3-one

# **SECTION 16.** Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R22	HARMFUL IF SWALLOWED.
R34	CAUSES BURNS.
R36	IRRITATING TO EYES.
R36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
R36/38	IRRITATING TO EYES AND SKIN.
R38	IRRITATING TO SKIN.
R41	RISK OF SERIOUS DAMAGE TO EYES.
R50	VERY TOXIC TO AQUATIC ORGANISMS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road - CAS NUMBER: Chemical Abstract Service Number

- CE50: Effective concentration (required to induce a 50% effect)

- CE NUMBER: Identifier in ESIS (European archive of existing substances)

# **AR-CO CHIMICA S.R.L.**

Revision nr. 1

Page n. 10/10

Dated 30/12/2014 Printed on 02/03/2015

## GOTA

CLP: EC Regulation 1272/2008

- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- **OEL: Occupational Exposure Level**
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- Directive 67/548/EEC and following amendments and adjustments
  Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
  Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
- 9. The Merck Index. 10th Edition
- 10. Handling Chemical Safety
- 11. Niosh Registry of Toxic Effects of Chemical Substances
- 12. INRS Fiche Toxicologique (toxicological sheet)
- 13. Patty Industrial Hygiene and Toxicology
- 14. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 15. ECHA website
- Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 05 / 07 / 08 / 11 / 12 / 15.