

## HALLES

### HIGHLY-CONCENTRATED SELF-POLISHING POLYMERIC METALIZED PROTECTIVE EMULSION



#### FEATURES AND USE

HALLES is a highly concentrated polymeric emulsion suitable for PVC, linoleum, rubber, marble, granite and agglomerate floors. Its high content of polymers, waxes and resins makes it possible to obtain, with just one coat, a protection that reaches top-level self-polishing quality and traffic-resistance. The film produced by HALLES is resistant to traffic and black heel marks. For maintenance use either low/medium speed as well as U.H.S. (ultra high speed) spraying systems.



#### METHOD OF USE & DILUTION :

**APPLICATION:** Perfectly remove the old wax using TAGO or RAPPER, then let dry. With the applicator, apply A SINGLE COAT of HALLES and let dry.

**MAINTENANCE:** Wet system with GREEN, GLOSSY or ASTRA - Dry system with SCHNELL (UHS).

#### DILUTION :

Ready to use.

#### PACK SIZE :

Jerrycan 5Kg – 4pcs/carton

#### TECHNICAL DATA :

Physical state: liquid

Colour: white

Odour: technical

pH: 8.34 +/-0.5

Specific weight: 1.033 +/-0.005 g/cm<sup>3</sup>

#### COMPOSITION :

See safety data sheet. Ingredients compliant with CE Reg. 648/2004.

#### CAUTIONS:

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.