		Devision on 7		
AR-CO Cł	Revision nr. 7 Dated 30/9/2014			
	Printed on 01/10/2014			
		Page n. 1/11		
	Safety data sheet			
SECTION 1. Identification of the subs	stance/mixture and of the company/unde	ertaking		
1.1. Product identifier				
Product name	INFYNITI ELKASAN LIGHT			
	ixture and uses advised against OR INDUSTRIAL / PROFESSIONAL USING ASCALER ACID DETERGENT FOR DAILY CLEANING			
1.3. Details of the supplier of the safety data sheet Name	AR-CO CHIMICA S.R.L.			
Full address	Via Canalazzo 22/24			
District and Country	41036 MEDOLLA (MO) ITALY			
	Tel. +39 053558890			
	Fax +39 053558898			
e-mail address of the competent person				
responsible for the Safety Data Sheet Product distribution by	reach@arcochimica.it AR-CO CHIMICA			
1.4. Emergency telephone number      For urgent inquiries refer to      Numeri telefonici dei principali Centri Antiveleni italiani (attivi 24/24 ore)Centro      Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca` Granda -Milano)      (H24)Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri -      Pavia)Centro Antiveleni di Bergamo 800 883300 (CAV Ospedale Riuniti -      Bergamo)Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi -      Firenze)Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)Centro				
	Antiveleni di Roma 06 49978000 (CAV Policlinico Umb Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli ORE UFFICIO / OFFICE HOURS 08:00-12:30 / 14:00-17	)AR-CO CHIMICA+39 053558890 (		
SECTION 2. Hazards identification.				
2.1. Classification of the substance or mixture.				
supplements). The product thus requires a safety datash	ne provisions set forth in EC Regulation 1272/2008 (CLF neet that complies with the provisions of EC Regulation 190 n and/or the environment are given in sections 11 and 12 o	7/2006 and subsequent amendments.		
2.1.1. Regulation 1272/2008 (CLP) and following an	nendments and adjustments.			
Hazard classification and indication:				
Eye Dam. 1 Skin Irrit. 2	H318 H315			
	01010			
2.1.2. 67/548/EEC and 1999/45/EC Directives and fo Danger Symbols:	llowing amendments and adjustments.			
Xi R phrases:				

	AR-CO	CHIMICA S.I	K.L.	Revision nr. 7 Dated 30/9/2014
	Printed on 01/10/2014			
	Page n. 2/11			
he full wording of the Ris	sk (R) and hazard (H) phrase	es is given in secti	on 16 of the sheet.	
2.2. Label elements.				
lazard labelling pursuant	to FC Regulation 1272/200	8 (CLP) and subse	equent amendments and supplemer	nts
••••••••••••••••••••••••••••••••••••••		- ( ,		
Signal words:	Danger			
olghar words.	Danger			
H318	Causes serious eye dam	nage.		
H315 EUH208	Causes skin irritation. Contains: (R)-p-mentha-1,8-diene			
	May produce an allergic	reaction.		
P280 P302+P352 P310	Wear protective gloves / IF ON SKIN: Wash with Immediately call a POIS	plenty of soap and		
Contains:	COCONUT OIL DIETHA	NOLAMIDE		
2.3. Other hazards.				
nformation not available.				
SECTION 3. Con	nposition/informati	on on ingred	lients.	
3.1. Substances.				
nformation not relevant.				
3.2. Mixtures.				
Contains:				
Identification. 2-BUTOXYETHANOL		Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
CAS. 111-76-2		10 - 30	Xn R20/21/22, Xi R36/38	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC. 203-905-0 INDEX. 603-014-00-0				
Reg. no. 01-21194751	08-36			
-	OL MONOMETHYL ETHER			
CAS. 34590-94-8		1 - 5		Substance with a community workplace exposure
		-		limit.
EC. 252-104-2				
EC. 252-104-2 INDEX				

# **INFYNITI ELKASAN LIGHT**

Revision nr. 7 Dated 30/9/2014

Printed on 01/10/2014

Page n. 3/11

COCONUT OIL DIETHANOLAMIDE			
CAS. 68603-42-9 EC. 931-329-6	1 - 3	Xi R38, Xi R41	Eye Dam. 1 H318, Skin Irrit. 2 H315
INDEX			
Reg. no. 01-2119490100-53-0013			
CAS. 5949-29-1 EC. 201-069-1	1 - 5	Xi R36	Eye Irrit. 2 H319
INDEX			
Reg. no. 01-2119457026-42			
SODIUM C9-22 ALKYL SEC SULFONATE			
CAS. 68188-18-1	1 - 5	Xn R22, Xi R36/38	Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC. 269-144-1			1010
INDEX			
Reg. no. 01-2119517577-32			
BRANCHED ALKYL ALCOHOL (C11-C13) ETHOXYLATES CAS. 68439-54-3 EC. 931-985-3	1 - 3	Xn R22, Xi R41	Acute Tox. 4 H302, Eye Dam. 1 H318
INDEX			
Reg. no. NO REGISTRATION NUMBER ( POLYMER) (R)-p-mentha-1,8-diene			
CAS. 5989-27-5	0 - 0,25	R10, Xi R38, Xi R43, N R50/53, Note C	Flam. Liq. 3 H226, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410, Note C
EC. 227-813-5			
INDEX. 601-029-00-7			
2-(2-(4-METHYL-3-CCLOHEXEN-1-YL)PROPYL) CYCLO-PENT			
CAS. 95962-14-4 EC. 404-240-0	0 - 0,25	N R50/53	Aquatic Chronic 1 H410
INDEX			
HEXYL ACETATE			
CAS. 142-92-7 EC. 205-5772-7	0 - 0,5	R10, N R51/53	Flam. Liq. 3 H226, Aquatic Chronic 2 H411
INDEX			
UNDECAN-4-OLIDE			
CAS. 104-67-6 EC. 203-225-4	0 - 0,5	N R51/53	Aquatic Chronic 2 H411
INDEX			

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet. T + = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F + = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

## **SECTION 4. First aid measures.**

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical

Revision nr. 7 Dated 30/9/2014

# **INFYNITI ELKASAN LIGHT**

Printed on 01/10/2014

Page n. 4/11

advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

### **SECTION 5. Firefighting measures.**

### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6.** Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Revision nr. 7 Dated 30/9/2014

## **INFYNITI ELKASAN LIGHT**

Printed on 01/10/2014 Page n. 5/11

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

## 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

## 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

United Kingdom	EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as
	amended).
Éire	Code of Practice Chemical Agent Regulations 2011.
OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive
	2000/39/EC.
TLV-ACGIH	ACGIH 2012

2-BUTOXYETHANOL						
Threshold Limit Value.						
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
WEL	UK	123	25	246	50	SKIN
OEL	IRL	98	20	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

### DIPROPYLENE GLYCOL MONOMETHYL ETHER **Threshold Limit Value.**

# INFYNITI ELKASAN LIGHT

Revision nr. 7

Dated 30/9/2014

### Printed on 01/10/2014

Page n. 6/11

Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
WEL	UK	308	50			SKIN
OEL	IRL	308	50			SKIN
OEL	EU	308	50			SKIN
TLV-ACGIH		606	100	909 (C)	150 (C)	

#### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

## **SECTION 9.** Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	brilliant pink
Odour	PEACH
Odour threshold.	Not available.
pH.	2,90 +/- 0,50
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not available.
Evaporation Rate	Not available.

# INFYNITI ELKASAN LIGHT

Revision nr. 7

Dated 30/9/2014

Printed on 01/10/2014 Page n. 7/11

Flammability of solids and gases Lower inflammability limit. Upper inflammability limit. Lower explosive limit. Upper explosive limit. Vapour pressure. Vapour density Relative density. Solubility Partition coefficient: n-octanol/water Auto-ignition temperature. Decomposition temperature. Viscosity Explosive properties Oxidising properties Not available. Not available. Not available. Not available. Not available. Not available. 1,015 +/- 0.025 COMPLETELY SOLUBLE IN WATER Not available. Not available.

### 9.2. Other information.

Information not available.

### **SECTION 10. Stability and reactivity.**

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER: may react with oxidising agents. When heated to decomposition it releases harsh and irritating fumes and vapours. 2-BUTOXYETHANOL: decomposes in the presence of heat.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL: can react dangerously with: aluminium, oxidising agents. Forms peroxide with air.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL: avoid exposure to sources of heat and naked flames.

#### 10.5. Incompatible materials.

Information not available.

#### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL: hydrogen.

Revision nr. 7

Dated 30/9/2014 Printed on 01/10/2014

# **INFYNITI ELKASAN LIGHT**

Page n. 8/11

## **SECTION 11. Toxicological information.**

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product. This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory trait. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

2-BUTOXYETHANOL LD50 (Oral). 615 mg/kg Rat LD50 (Dermal). 405 mg/kg Rabbit LC50 (Inhalation). 2,2 mg/l/4h Rat

## **SECTION 12. Ecological information.**

### 12.1. Toxicity.

(R)-p-mentha-1,8-diene EC50 - for Crustacea. 0,48 mg/l/48h

### 12.2. Persistence and degradability.

Information not available.

#### 12.3. Bioaccumulative potential.

Information not available.

#### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%. 12.6. Other adverse effects.

Information not available.

### **SECTION 13.** Disposal considerations.

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Avoid littering. Do not contaminate soil, sewers and waterways. CONTAMINATED PACKAGING

	AR-CO CHIMICA S.R.L.	Revision nr. 7
		Dated 30/9/2014
	Printed on 01/10/2014	
		Page n. 9/11
Contaminated packaging mus	st be recovered or disposed of in compliance with national waste man	pagement regulations
SECTION 44 Trans	nort information	
SECTION 14. Trans	port mornation.	
	s under current provisions of the Code of International Carriage of D ngerous Goods Code (IMDG), and of the International Air Transport A	
SECTION 15. Regu	latory information.	
15.1. Safety, health and en	nvironmental regulations/legislation specific for the substance o	r mixture.
Seveso category.	None.	
Restrictions relating to the pro	oduct or contained substances pursuant to Annex XVII to EC Regulati	ion 1907/2006.
Product.		
Point.	3	
Substances in Candidate List	<u>(Art. 59 REACH).</u>	
None.		
Substances subject to authori	sarion (Annex XIV REACH).	
None.		
Substances subject to exporta	ation reporting pursuant to (EC) Reg. 649/2012:	
None.		
Substances subject to the Rot	tterdam Convention:	
None.		
Substances subject to the Sto	ockholm Convention:	
None.		
Healthcare controls.		
Workers exposed to this chen workers' health and safety are	nical agent must not undergo health checks, provided that available e modest and that the 98/24/EC directive is respected.	risk-assessment data prove that the risks related to the
Ingredients according to Regu	ulation (EC) No 648/2004	
less than 5 % anionic s	urfactants, non-ionic surfactants	
perfumes, Limonene, Linalool		
preservation agents : 1,2-ben	zisotiazol-3(2H)-one / 2-metil-2H-isotiazol-3-one	
45.0 Oberningt		
15.2. Chemical safety asse	essment.	

# **INFYNITI ELKASAN LIGHT**

Revision nr. 7

Dated 30/9/2014

Printed on 01/10/2014 Page n. 10/11

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16.** Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10	FLAMMABLE.
R20/21/22	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
R22	HARMFUL IF SWALLOWED.
R36	IRRITATING TO EYES.
R36/38	IRRITATING TO EYES AND SKIN.
R38	IRRITATING TO SKIN.
R41	RISK OF SERIOUS DAMAGE TO EYES.
R43	MAY CAUSE SENSITISATION BY SKIN CONTACT.
R50/53	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

LEGEND:

ADR: European Agreement concerning the carriage of Dangerous goods by Road
 CAS NUMBER: Chemical Abstract Service Number

- CE50: Effective concentration (required to induce a 50% effect) - CE NUMBER: Identifier in ESIS (European archive of existing substances)

CLP: EC Regulation 1272/2008

- DNEL: Derived No Effect Level

# **INFYNITI ELKASAN LIGHT**

Revision nr. 7

Dated 30/9/2014

Printed on 01/10/2014 Page n. 11/11

- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- Regulation (EC) 1272/2008 (CLP) of the European Parliament
  Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament 8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
- 9. The Merck Index. 10th Edition
- 10. Handling Chemical Safety
- 11. Niosh Registry of Toxic Effects of Chemical Substances
- 12. INRS Fiche Toxicologique (toxicological sheet)
- 13. Patty Industrial Hygiene and Toxicology
- 14. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 15. ECHA website
- Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 02 / 04 / 05 / 07 / 08 / 11 / 12.