MAYOR

FLOOR PROTECTION



HIGH-RESISTANCE SELF-POLISHING ACRYLIC EMULSION

FEATURES AND USE

Blend of special waxes and acrylic resins for the protection of hard surfaces, excellent for restoring gloss and protection of floors worn out by foot traffic. Thanks to its special formula, it ensures a mirror-like gloss similar to lead polishing. Suitable for obtaining a shiny and glossy result on indoor marble, granite, terrazzo/stoneware cement tiles, terracotta, stoneware, PVC, linoleum and porous floors.

Advantages: patches floor micro porosity, covers small scratches making the floor more compact; creates a mirror-like bright transparent gloss effect, does not create halos; ensures longer protection compared to other waxes; easy to lay and maintain; free from hazardous substances during and after application; protects, for some minutes, delicate floors from accidental damages caused by acids substances.

METHOD OF USE and DILUTION

Ready to use.

Shake before use.

Use at temperatures between $+10^{\circ}$ C and $+30^{\circ}$ C.

Apply the product preferably on surfaces cleaned and without old waxing.

Spread a thin, even coat on dry floor. Let dry before laying a second coat. No polishing needed. Routine cleaning: do not use alcohol-based/acid-based/solvent-based/ammonia-based detergents.

Clean fleece /spreading tools: wash with water





PACK SIZE

5kg

4pcs/cart

Art. code: MA5

TECHNICAL DATA

Physical state: liquid Colour: milk white Odour: scented pH: 7,5 +/-0,50

Density: 1,018 +/-0,025 Kg/L

Flash point: > 60°C

YIELD: 22-35 mq/L per coat depending on floor porosity

COMPOSITION

See safety data sheet. Ingredients compliant with CE Reg. 648/2004

CAUTIONS

See safety data sheet.

DRYING TIME

DUST DRY: 2 hours FOOT TRAFFIC: 4 hours COMPLETELY DRY: 48 hours

STORAGE INSTRUCTIONS

Keep container well closed Store in a cool, frost-free, dry place

Keep away from UV

