

## FLOOR PROTECTION



## WATER&OIL-REPELLENT SEALING TREATMENT

### FEATURES AND USE

Water and oil repellent treatment for sealing and proofing cement, cotto, linoleum, quartz cement, clinker and natural stone floors. Particularly suitable on industrial floors and surfaces exposed to the weather.

Its composition makes it resistant to alkaline detergents, acid substances (citric acid, phosphoric acid, sulphamic acid etc..), oils of mineral and vegetal origin and alcohol.



### METHOD OF USE

Before treating it with SILPAV, clean the floor thoroughly, preferably with MISTRAL at 5%-8%, then rinse. Lay two coats of SILPAV using a paint roller or a flat brush, let dry for about one hour between the first coat and the second one. Aerate the room during and after treatment.

### DILUTION

Ready to use

### STORAGE INSTRUCTIONS

Sensitive to frost

### PACK SIZE

Drum Art. code: 5750  
10kg

### TECHNICAL DATA

Physical state: liquid

Colour: colourless - transparent

Odour: technical

pH: n.d.

Relative density: 0,904 Kg/L

Water solubility: insoluble

Flash point: >23°C

Yield: 10-16 mq/L per coat depending on floor porosity

### COMPOSITION

See safety data sheet. Ingredients compliant with CE Reg. 648/2004

### CAUTIONS

See safety data sheet.