

HEAVY DUTY CLEANING

STRAT

SOLVENT-BASED SUPER WAX STRIPPER



FEATURES AND USE

Specific wax stripper for fast removal of old wax layers. Strat is suitable for wax stripping from resilient floors (PVC, linoleum, rubber, etc.) and stone floors. It makes a strong degreasing and emulsifying action against greasy dirt also on cement, cotto, grès tiles floors etc. and remove the paraffin. Thanks to its odourless and detaching power even at low concentration, it is suitable to be used in poorly ventilated areas.



METHOD OF USE :

Machine use: dilute 1L in 8-15L of water depending on the thickness of the layer to be removed. Let act for a few minutes and then remove it with a wet & dry vacuum cleaner.

Manual use: Dilute 1L in 8L of water.

For wax spray stripping (dry): dilute 1L in 3L of water. Protect the surface with MAYOR or KOMETA.

DILUTION :

5-20% (da 500-2000g in 10L water) according to the operation

PACK SIZE :

Jerrycan 5Kg – 4pcs/carton

TECHNICAL DATA:

Physical state: liquid

Colour: intense yellow

Odour: technical

pH: 13,0 +/- 0,50

Relative density: 0,931+/-0,009 Kg/L

COMPOSITION :

See safety data sheet. Ingredients compliant with CE Reg. 648/2004

CAUTIONS :

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Harmful if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage.

May cause respiratory irritation.

Wear protective gloves / protective clothing / eye protection / face protection.

IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Store in a well-ventilated place. Keep container tightly closed.

Contains: POTASSIUM HYDROXIDE ETHANOLAMINE 2-BUTOXYETHANOL



Danger



AR-CO CHIMICA s.r.l. Via Canalazzo, 22/24 – 41036 MEDOLLA - ITALY
Tel +39 0535.58890 – info@arcochimica.it – www.arcochimica.it

PROFESSIONAL USE