

## PROTECTION

# T.P.

## ANTI-DUST ACRYLIC SEALER



### FEATURES AND USE

T.P. is sealer suitable for indoor floors like concrete and asphalt. It is excellent for preparing old and worn out floors like PVC, rubber and linoleum for being treated with metalized wax.



### METHOD OF USE & DILUTION :

On a clean and dry floor, lay a first and uniform coat of T.P. let dry, then lay a second one, criss-crossing the first.

### DILUTION :

Ready to use.

### PACK SIZE :

Jerrycan 5Kg – 4pcs/carton

### TECHNICAL DATA :

Physical state: liquid

Colour: white

Odour: odourless

pH: 7.70 +/- 0.60

Specific weight: 1.012+/-0.008 g/cm<sup>3</sup>

### COMPOSITION :

See safety data sheet. Ingredients compliant with CE Reg. 648/2004.

### CAUTIONS :

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Causes serious eye irritation.

Wear protective gloves / protective clothing / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice / attention.



**Warning**



AR-CO CHIMICA s.r.l. Via Canalazzo, 22/24 – 41036 MEDOLLA (MO)  
Tel 0535.58890 – info@arcochimica.it – www.arcochimica.it

**PROFESSIONAL USE**