

HEAVY DUTY CLEANING

TAGO

LOW FOAMING WAX STRIPPER



FEATURES AND USE

Tago is a low foaming concentrated wax stripper, particularly suitable to remove old metallized wax from PVC, linoleum, stone, rubber floors, etc.

Thanks to its strong action, it makes it easily removes old wax even manually where machine use is not possible(steps, corners etc.). It acts within a few minutes.



METHOD OF USE :

Spread the solution on the floor and let it to act for a few minutes. Using the single-brush machine fitted with green or black abrasive disk make the mechanical action on the floor, vacuum the solution and rinse thoroughly.

On linoleum floors, reduce dilution to 5% and check colour fastness.

Avoid undiluted product contact with protected floors.

DILUTION :

10-20% (1-2L in 10L water).

PACK SIZE :

Jerrycan 5Kg – 4pcs/carton

TECHNICAL DATA :

Physical state: liquid

Colour: yellow

Odour: technical

pH: 13,50 +/- 0,50

Relative density: 1,008+/-0,006 Kg/L

COMPOSITION :

See safety data sheet. Ingredients compliant with CE Reg. 648/2004

CAUTIONS :

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard statements: Causes severe skin burns and eye damage. May cause respiratory irritation.

Precautionary statements: Wear protective gloves / protective clothing / eye protection / face protection.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or doctor / physician.

Store in a well-ventilated place. Keep container tightly closed.

Contains: ETHANOLAMINE



Danger



AR-CO CHIMICA s.r.l. Via Canalazzo, 22/24 – 41036 MEDOLLA - ITALY
Tel +39 0535.58890 – info@arcochimica.it – www.arcochimica.it

PROFESSIONAL USE